# FORTRESS



# **Industrial Access Control**

# amGardpro





#### Introduction to FRANK

# Fortress RFID Access Network Keys

Interlocks control when you can access equipment safely, Frank controls who can access equipment safely.

By integrating readers to suit the existing site RFID access cards into a Fortress device and providing a software based access approval control system; FRANK can be integrated into automation systems with simple input / outputs to a PLC.

Data of who, when and where from access events is collated to a central point within facilities to allow for viewable events lists and data insights that can support efficiency analysis.

Fortress supports common card types including:

- 13.56MHz ISO 15693
- 13.56MHz with manufacturer's specific protocol
- 13.56MHz ISO 14443A
- 125kHz with manufacturer's specific protocol

#### **Control Access**





### Manage Productivity



Control access to a large automated area with multiple doors and existing safety system. In addition, employees are permitted to record their entry through one door and exit through another door to the area. Once all employees have signalled they are outside the guarding, the FRANK system reports the area is empty to the PLC and the reset procedure can be undertaken.



The existing trapped key system fitted in this scenario allows access only when the control system is isolated by a solenoid controlled trapped key device. Door interlocks release 3 personnel keys to prevent restart while operators enter the safeguarded space. RFID badges are used to restrict the start of the trapped key sequence to trained operators.



Every hour during brick production, a sample brick must be extracted from the process and tested to ensure the correct clay conditions. The FRANK system automates the record keeping of the brick acceptance / rejection to provide management reporting. Outputs from the FRANK unit can be fed into the machine control system to restart the manufacturing process.





Access to hazardous areas of the slitting line is safeguarded by guard locking devices with the request to enter performed by an authorised employee presenting their RFID badge to the interlock. The FRANK system additionally provides access via RFID badges to the line side HMI restricting process change to only approved employees. Data is collected within the FRANK system of all RFID badge and interlock access events.





#### FRANK Standard Device Configurations



RFID reader configured alongside pushbutton control elements to be used as a supporting device to a quality inspection system.

Pushbuttons can be programmed to become active to restart the process only after an authorised operator has conformed the process status.



Interlock with RFID reader integration configuration including forced extracted key mechanism.

Operators are required to remove the personnel key from the lock before the guard will open. Guard is prevented from being closed while operator retains the key.

#### Selecting a FRANK Controller



636

### Programming a FRANK System

#### **Control System Inputs**

The Fortress access control system is designed to be programmed as simple inputs to Fortress amGard*pro pro*Net devices. These additional inputs are shown below. For safe, unsafe, and other extended IO inputs possible in the *pro*Net range please see alternative Fortress documentation.

Description		Bits							
		0	1	2	3	4	5	6	7
RFID									
7-14 Bytes	RFID LSB first (reserved)								
Access Control Inputs									
Byte 0		Error	Access granted	Access denied	Cell empty	-	-	-	-
Byte 1	Additional permissions*	Additional permission Bit 0	Additional permission Bit 1	Additional permission Bit 2	Additional permission Bit 3	Additional permission Bit 4	Additional permission Bit 5	Additional permission Bit 6	Additional permission Bit 7
Access Control Outputs									
Byte 0		Reset							
Access control bits will pulse high for 100ms as determined by the access control system. If a user is permitted to unlock the interlock, access granted will pulse high. If a user is not permitted to unlock the interlock, access denied will pulse high. When the interlock is relocked, cell empty will pulse high. Error Bit 0 will go high if unit is disconnected from a local controller.									
*Additional permissions are set in the system software as a whole byte, giving 256 possible additional permissions. Alternatively, individual bits could be used.									

### Selecting a FRANK Controller

#### Step 1. Install

Install Fortress devices and establish communication with the PLC



Auto-discover Fortress devices on the FRANK local access controller

#### Step 3. Import

Configure of master access controller software. Import users and card details







# FORTRESS

# FORTRESS

We have the peace of mind that our workers are safe and protected by Fortress equipment.

# -FORTRESS

Fortress' best quality is providing each customer the most robust and safe solution - all while being completely customizable and retaining a high level of quality.

## **FORTRESS**

Fortress is best at providing customised solutions at a rapid turnaround - reacting immensely to a challenge to put the customer's needs first.



# -FORTRESS<sup>,</sup>

We value suppliers that can help navigate the standards and provide guidance that is directly linked to our applications.



## Fortress Global Offices and Manufacturing Facilities

**Fortress Interlocks Ltd S** +44 (0)1902 349000

Fortress Interlocks USA +1 (859) 578 2390

**Fortress Interlocks Pty Ltd S** +61 (0)3 9771 5350 Fortress Interlocks China • +86 (021) 6167 9002

Fortress Interlocks India



www.fortress-safety.com

#### Notes



A Halma company

April 2025 v1.6